HEWLETT-PACKARD



QuietJet Printer Series



The flexible QuietJet Printers offer the best features of personal printing ...without the noise.

You get exceptionally **quiet**, **quality** printing for word processing, data base management, and computer graphics. For spreadsheets, letters, or labels as you need.

QuietJet Printers work with most major personal computers. And it's supported on a host of popular industry-standard software packages.

Quality Printing

You get high-quality printing: near letter-quality (NLQ) for important letters and reports and graphics in three densities for impressive charts and illustrations. Even when printing quick drafts, you get sharp characters for easy reading and a professional look.

User Convenience

The disposable, drop-in ink print cartridge combines innovation with true user convenience. The friendly key panel allows you to select NLQ, draft, and compressed printing at the touch of a button.

Features

·Quiet printing

Quality text and graphics

- -NLQ at 40/48 cps
- -160/192-cps draft printing
- -High-quality graphics

•Excellent compatibility

- •Comprehensive print features -six print pitches -near letter-guality (NLQ)
- -superscripts and subscripts
- ·Convenient keypanel
- Paper-handling convenience
- -last-form tearoff
- -paper advance knob
 -Adjustable tractors
- •Expandable, tailorable

Benefits

You can talk on the telephone; you can print what you need without disturbing anyone.

Turns out professional-looking letters and reports and fast, easy-toread spreadsheets and charts.

It hooks up with a variety of PCs and portables-HP, IBM or Apple. And it's supported on most popular industry-standard software.

Your customer can change the print size and use print enhancements to highlight, clarify, or simply get more information on a page.

Select NLQ, draft and compressed print with just one keystroke.

Inserting, adjusting, even tearing off of paper is quick and easy to manage. And there is no paper waste.

As application needs grow, your customer can get dealer-installable RAM for special applications.

Print Sample

Print quality is enhanced over common dot matrix printers by 19×16 (draft) and 19×32 (NLQ) character cells which provides high resolution characters in bold face or underlining and six print pitches as shown here. This is compressed print.

```
This is normal print.
This is Expanded-Compressed print.
This is Expanded print.
<u>This is NLQ print.</u>
This is draft print
```

Supplies and Accessories

Supplies: Meeting Everyday Needs

The HP JetSeries Printer is actually a system, composed of the printer, an innovative disposable ink print cartridge, and HP JetPaper. Together they provide **quiet** operation and **quality** printing, a winning combination.

A wide range of JetSeries supplies support quality printing on ThinkJet and QuietJet Printers. HP's JetSeries supplies and accessories now include wide paper for QuietJet Plus spreadsheet printing, address labels, even singlecolor print cartridges in black, red, blue or green.

To order, simply see your local dealer. Or, for 24-hour delivery, order direct from Hewlett-Packard Direct Marketing by calling the toll-free number (800-538-8787).



Description	Order No
Black ink print cartridge. Fits ThinkJet and QuietJet printers.	92261A
Red ink print cartridge. Fits ThinkJet and QuietJet printers.	51605R
Blue ink print cartridge. Fits ThinkJet and QuietJet printers.	51605B
Green ink print cartridge. Fits ThinkJet and QuietJet printers.	51605G
Z-fold JetPaper. 8½"×11" finished size. 500 sheet box, 20 lb., microperforated.	51630A
Wide Z-fold JetPaper. 14%"×11". 500 sheet box, 20 lb.	51630B
Wide Z-fold JetPaper. 14%"×11". 2500 sheet carton, 20 lb.	51630D
CutSheet JetPaper. 8½"×11". 500 sheet box, 20 lb., single sheets.	51630J
Z-fold JetPaper. 8½"×11" finished size. 2500 sheet carton, 20 lb., microperforated.	92261N
JetLabels. 2000 address labels $(3.5" \times 15/16"$ labels—two across), 9.5" form width. Pressure sensitive.	51630L
QuietJet Plus Printer dust cover.	92250W
QuietJet Printer dust cover.	92250X
QuietJet Plus Printer stand.	92261T
QuietJet Printer stand.	92261U
QuietJet Series wire paper catcher. (requires printer stand).	92261G
Jetstart software program. Modifies standard Macintosh application discs to run with the QuietJet Printer series.	35177M



Specifications

Print Speed	160 cps, draft mode (bidirectional, optimized path), 10 cpi 40 cps, NLQ mode (unidirectional, optimized path), 10 cpi 192 cps, draft mode (bidirectional, optimized path), 12 cpi 48 cps, NLQ mode (unidirectional, optimized path), 12 cpi	Paper Handling	 Friction feed for single sheets Tractor feed for continuous fan-fold paper Paper widths: 10.2 cm (4") minimum 38.1 cm (15") QuietJet Plus maximum; 24.8 cm (9¾") QuietJet maximum. Note: We are interested in quality and cannot guarantee optimal print quality or printer reliability on non-HP paper. 	
Character Cell Structure Character Sets	19 (h)×16 (v), draft mode 19 (h)×32 (v), NLQ mode HP Roman 8	Key Panel	Buttons: On-line, Form Feed, Line Feed LED indicators: NLQ mode, Draft mode, Compressed mode	
	128 US ASCII (upper and lower case and control codes) Supports Danish, Dutch, English, Finnish, French, German, Nor- wegian, Portuguese, Spanish and Swedish ISO 7-bit languages Supports French, German, Italian, Por- tuguese, Spanish, Swedish/Finnish, Nor- wegian, United Kingdom, and US ASCII IBM PC character set (US and Europe).	Dual I/O Interface	Centronics parallel and RS-232C serial, standard	
		Power Requirements	Power modules 100 volts AC (+10%, -10%) 47.5-63 Hz 120 volts AC (+10%, -10%) 47.5-63 Hz 220 volts AC (+10%, -10%) 47.5-63 Hz 240 volts AC (+10%, -10%) 47.5-63 Hz Power consumption at 20 VAC 10 W maximum non-printting	
Graphics	96×96 dots per inch dot-addressable graphics 192×96 dots per inch, double density mode 192×192 dots per inch, quadruple density mode		18 W maximum non-printing 18 W maximum printing Maximum heat output 61.5 BTU/hour	
		Environmental	Temperature: 10° to 40°C (50° to 104°F), operating; -20° to 60°C (-4° to 140°F), storage	
Print Modes Normal—10 cpi	QuietJet: 80 characters/line QuietJet Plus: 132 characters/line		Humidity: 10 to 90% RH, non-condensing Acoustics: (per ISO DP7779 standard) Sound pressure level-L _{pa} : <48.5 dB(A)@1 meter bystander position	
Normal—12 cpi	QuietJet: 96 characters/line QuietJet Plus: 158 characters/line	Dimensions	QuietJet: 395 mm (15.5") W×118 mm (4.65") H×214 mm (8.43") D QuietJet Plus: 527 mm (20.75") W×121 mm (4.76") H×221 mm (8.7") D	
Expanded—5 cpi	QuietJet: 40 characters/line QuietJet Plus: 66 characters/line			
Expanded—6 cpi	QuietJet: 48 characters/line QuietJet Plus: 79 characters/line	Weight	QuietJet: 3.9 kg (8 lb., 9 oz) QuietJet Plus 4.7 kg (10 lb., 7 oz.)	
Compressed—21.3 cpi	QuietJet: 170 characters/line QuietJet Plus: 281 characters/line	Buffer Size	2K bytes, expandable up to 18K	
Expanded-Compressed — 10.7 cpi	QuietJet: 85 characters/line QuietJet Plus: 141 characters/line Draft print; a variation of Letter Gothic font NLQ print; a variation of Courier font	Estimated Usage	Less than 40 pages per day	
		Product Certifications	UL, CSA, FEI, NEMKO, TUV, VDE/FTZ, IEC compliance, FCC Class B Certified per	
Operational Modes	Switch selectable HP/ alternate (Epson-type) modes		FCC Rules, Part 15, Subpart J, when used with a Class B computing device. Any questions concerning regulatory compliance	
Command Language and Emulation	HP Printer Command Language PCL level 1+; Epson MX80 emulation		should be directed to your local HP sales office.	
Software Support	The QuietJet Printers are fully supported on major software packages. Additional sup- port is being provided on a regular basis.			

Interface and Cable Requirements

Interface and Cable Requirements

HP SYSTEM SERIES MODEL	PRINTER I/O	HOST INTERFACE	CABLE	
Vectra PC	Parallel	HP 24540A Serial/Parallel Interface Card	24542D	
	Serial	HP 24540A Serial/Parallel Interface Card	24542G	
		HP 24541A Dual Serial Interface Card	24542G (using 9 pin connector) 13242G (using 25 pin connector)	
Touchscreen PC	Serial	Built-in	13242G	
Portable PC	Serial	Built-in	92221P	
HP Terminals (2392A, 2393A, 2394A, 2397A)	Parallel	Opt 093 or HP 40210P*	40242D	
	Serial	Opt 092 or HP 40210R*	40242G	
NON-HP SYSTEM SERIES MODEL	PRINTER I/O	HOST INTERFACE	HP CABLE #	NON-HP CABLE #
Apple II, II+, IIe	Parallel	Apple II Parallel Interface Card or Grappler+	Not Available	Apple #590-0042
	Serial	Apple Super-serial Card	17355M	Apple #590-0037
Apple IIc	Serial	Built-in	92219N	Apple # 590-0191-A
Macintosh**	Serial	Built-in	92219M	Standard Macintosh Printer Cable
IBM PC, PC / XT	Parallel	IBM Parallel Printer Adaptor	92219K	IBM Parallel Printer Cable
	Serial	IBM Asyn. Com. Adaptor	17255D or 13242H	Not available
IBM AT '	Parallel	IBM Serial/Parallel Adaptor	24542D	IBM Parallel Printer Cable
IBM AT	Serial	IBM Serial/Parallel Adaptor	24542G	

*Host interface to order when adding QuietJet Printer to standard terminal. **Requires software driver (PN35177M, available from DMK)

Ordering Information

HP 2227A QuietJet Plus Personal Printer HP 2228A QuietJet Personal Printer

Standard unit includes: Print head cartridge, packet of fanfold ink-jet paper, power module/cord, owner's manual, and warranty card.

Centronics-type and RS-232C-type cables must be ordered separately. Non-HP interface boards and cards must be ordered through the personal computer supplier.



Hewlett-Packard Personal Computer Group 10520 Rigeview Ct. Cupertino, CA 95014

In Canada, write: Hewlett-Packard Marketing Department 6877 Goreway Drive Mississauga, Ontario Canada, L4V1M8 For the dealer nearest you: In U.S.A., call (800) FOR-HPPC In Canada, call (800) 387-3867