HP 2225 Family ThinkJet Printers





The low-cost HP 2225 family of personal printers provides fast, quiet printing for office, factory, home, or on-the-go. For permanent copies and portable printing, for high-quality, professional-looking text, the HP 2225 Family offers an exceptional solution via an all-new approach to ink-jet printing.

Simplicity of Design for User Convenience

The HP 2225 Family features a new and unique high-technology ink-jet print head system that is encased in a single disposable cartridge. There are no reservoirs to fill and virtually no mess. When the print head is empty, after about 500 pages of normal printing, you simply open the front window of the printer, pull a tab down, lift the old cartridge out, and insert the new one in place. Push the tab back up, close the print window; and you're off again.

Printing Flexibility

For highlighting and print variation, you can choose from four different print pitches. And you can print your text in boldface or underline in just one pass without sacrificing throughput. In addition, you get clear, distinct graphics with up to 192 x 96 dots per inch resolution.

Since the printer utilizes both friction feed and pin feed, you can use either single sheets or continuous fanfold paper depending on your application needs. The adjustable paper-feed mechanism allows you to use either $8\frac{1}{2} \times 11$ -inch or 21.0 x 29.7-centimeter (A-4 size) paper.

Features:

- 150-cps ink-jet printing
- 11 x 12 dot-matrix character cell
- Quiet 50 dBA printing
- Comprehensive print features -four print pitches -underline and bold
 - -Roman8
- -printable control codes
- Disposable print head
- Compact and lightweight
- Portable operation (HP2225B)
- Variety of interfaces
- Pin or friction feed

Graphics

Benefits and Advantages:

Delivers high throughput and permanent copies of your memos, graphics, reports, and spreadsheets. Your printed text is easy to read and professional looking. Suitable for any environment because noise is not a factor. Allows you to highlight and vary your output to meet your different printing needs.

Quick, clean, print head changes are accomplished in seconds, so you can get back to the business of printing with a minimum of interruption. It matches up well with the smallest of computers and tucks neatly into one half of a five-inch briefcase. Utilizes a rechargeable battery pack that will allow you to print up to 200 normal pages of type on one charge. You can hook it up with a variety of personal computers-Hewlett-Packard, IBM, Apple, Texas Instruments and Compaq to name a few. Allows you to use continuous

fanfold paper or cut sheets. Produces permanent copies of your graphics displays.

Print Sample

Print quality is enhanced over common dot matrix printers by an 11×12 character cell which provides high resolution characters in boldface or underline modes and four print pitches as shown here.

Compressed (142 characters/line) Normal (80 characters/line) Expanded compressed (21 ch

Expanded compressed (71 characters/line) Expanded(40 characters/line)

Specifications

PRINT SPEED

150 characters per second Bidirectional, optimized path CHARACTER STRUCTURE

11 x 12 character cell CHARACTER SETS

HP Roman8

128 USASCII (upper and lower case and control codes)

Supports Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Portuguese, Spanish, and Swedish

ISO 7-bit languages (HP 2225C only)

Supports French, German, Swedish, Spanish, United Kingdom, and USASCII

GRAPHICS

96 x 96 dots per inch dot-addressable raster graphics 192 x 96 dots per inch dot-addressable raster graphics in

high-density mode

PRINTING FORMAT

Print pitch (characters per inch)

21.3-Compressed

12.0-Normal

6.0—Expanded

10.7-Expanded Compressed

Line Length (characters per line) 142—Compressed

80—Normal

- 40—Expanded
- 71 Expanded Compressed
- Variable line spacing (lines per inch) 6,8

PAPER HANDLING

Friction feed for single sheets Pin feed for continuous fanfold paper Paper widths 8-1/2 x 11-inch (U.S. standard) 21.0 x 29.7-centimeter (metric A4)

For best results, use HP ink-jet paper. All paper should be tested for satisfactory feeding, registration and print quality

CONTROLS AND INDICATORS

Power on indicator Paper out indicator Top of form button Line feed button Form feed button

1000 bytes

POWER REQUIREMENTS

Input voltage (HP 2225A and 2225C) 120 volts AC (+5%, -10%); 47.5-63Hz Input voltage (HP 2225B) Uses internal battery power supply Power Consumption (HP2225A and 2225C) 1 VA maximum non-rinting 8 VA maximum printing BUFFER SIZE

INTERFACES AND POWER SOURCES

HP-IB, AC line power (HP 2225A) HP-IL, DC battery power (HP 2225B) Centronics parallel, AC line power (HP 2225C)

ENVIRONMENTAL CONDITIONS

Temperature, free space ambient 10° to 40° C (40° to 104° F) operating 20° to 60° C (-4° to 140° F) non-operating

Humidity

10% to 90% RH, non-condensing Acoustics (per ISO DP7779 standard) Sound pressure level—L_{wa}: <50 dB(A) @ 1 meter bystander position

PHYSICAL SPECIFICATIONS

206mm (8.1")D x 292mm (11.5")W x 89mm (3.5")H 3.36kg (7.4 lbs.) HP 2225À net weight 2.5kg (5.5 lbs.) HP 2225B net weight 3.1kg (6.8 lbs.) HP 2225C net weight

PRODUCT CERTIFICATIONS

UL, VDE/FTZ, CSA, EI, NEMKO, KEMA, TUV, SEV, IEC Compliance. FCC Class B Certified per FCC Rules, Part 15, subpart J, when used with a Class B computing device.

ESTIMATED TYPICAL USAGE Less than 40 pages per day.

Interface and Cable Requirements

PRINTER

MODEL

2225B

2225B

2225B

2225A

2225B

2225C

2225C

PRINTER

82160A

82401A

built-in

82937A

82938A

82949A

built-in

INTERFACE

CABLE

82957A

82167A, B, or D

82167A, B, or D

82167A, B, or D

10833A, B, C, D

82167A, B or D

Ordering Information

HP 2225 A, B, or C PRINTER

Standard unit includes:

Print head cartridge, packet of fanfold ink-jet paper, owner's manual, and warranty card. The HP 2225A and 2225C include a power cord. The 2225B includes a 1-meter HP-IL cable, battery pack, and a recharger.

HP-IB and Centronics-type cable must be ordered separately.

Non-HP interface boards and cards must be ordered through the personal computer supplier.

Supplies and Accessories

82199A Battery pack for HP 2225B 92261A Print head cartridge (1) 92261B Print head cartridges (pack of 10) 92261M Ink-jet paper-single sheets (4 packs of 500) 92261N Ink-jet paper-fanfold paper (2500 sheets) 92261S Acrylic print stand

Most supplies can be ordered via the HP Computer Users Catalog. Call for immedi-

ate price and availability information.				Non-HP interface boards and cards must be ordered through the personal com-			
Location	Telephone Number	Location	Telephone Number	puter supplier.			
United States California	800-538-8787 408-738-4133	The Netherlands South Africa	020-470639 802-5111 53-7954 28-4178 416-671-8383 1-800-268-6982 1-800-387-3417	SYSTEM SERIES MODEL	PRINTER MODEL	PRINTER INTERFACE	CABLE
United Kingdom France	0734-792868 0734-792959 (6) 928 32 64	Canada		Apple II, II + , Ile	2225C	Grappler + or Epson 8131 or 8132	
Belgium/Luxembourg Switzerland		Toronto Local Ontario Ouebec		IBM PC, PC XT	2225C	IBM parallel printer interface	IBM parallel printer cable
West Germany	07031-142829	British Columbia	112-800-387-3154	TI PC	2225C	built-in	TI 2223106-0001
	07031-223133	Other Provinces Sweden	1-800-387-3154 08-7502027 08-7502028	*The HP85 also requires an HP 00085-15002 Plotter/Printer ROM. The HP85 does not require the 10833 cable if there are no other peripherals attached.			

SYSTEM

HP 718

HP 85*

HP 86A

SERIES MODEL

HP 41C, CV, CX

HP 75C and D

For more information, call your local HP Sales Office or Regional Office: East (301) 948-6370 • Midwest (312) 255-9800 • South (404) 955-1500 • West (213) 877-1281. Or write to Hewlett-Packard: U.S.A. - 1820 Embarcadero Road, Palo Alto, CA 94303. Europe: P.O. Box 999, 1180 AZ Amstelveen, The Netherlands. Canada: 6877 Goreway Drive, Mississauga, L4V 1M8, Ontario. Japan: YHP Ltd., Ohashi 29-21 Takaido-Higashi 3-chome, Suginami-ku, Tokyo 168.

HP 86B and 87 2225A built-in 10833A, B, C, D Series 100 2225A built-in 10833A, B, C, D Touchscreen Touchscreen MAX Series 200 2225A built-in 10833A, B, C, D